



RAASI[®]
Pumps - Pipes - Cables

**V5
MIXED
FLOW
PREMIUM**

V5 MIXED FLOW PREMIUM

(Suitable For 6" And Above Bore Dia)

Motor: Premium motor with ss body, Copper Rotor,

Pump: Premium Pump with C.I bowl set & SS Impeller
3Phase, 415/440 Voltage



PER STAGE: 30 FEET HEAD

Model No.	H.P	Stage	NRV SIZE 65MM (2.5")	DISCHARGE IN LPM								PRICE
				500	470	435	400	300	200	150	100	PUMP SET
5RSMTM80-4	3.00	4		12	15	18	21	24	27	30	33	34190
5RSMTM80-6	5.00	6	TOTAL	20	24	27	30	36	42	45	49	39900
5RSMTM80-8	6.00	8	HEAD IN	28	32	36	40	44	48	56	65	45610
5RSMTM80-10	7.50	10	METERS	35	40	45	50	55	60	70	82	53360
5RSMTM80-12	10.00	12		42	48	54	62	80	84	90	96	61050

Model No.	H.P	Stage	NRV SIZE 65MM (2.5")	DISCHARGE IN LPM								PRICE
				450	425	395	365	310	250	185	130	PUMP SET
5RSMTM100-3	3.00	3		9	11	13	15	17	19	21	25	32610
5RSMTM100-5	5.00	5	TOTAL	15	20	23	25	27	30	36	42	38320
5RSMTM100-6	6.00	6	HEAD IN	18	24	27	30	33	36	42	50	42450
5RSMTM100-8	7.50	8	METERS	28	32	36	40	44	48	56	65	50200
5RSMTM100-10	10.00	10		35	40	45	50	55	60	70	82	56140

Model No.	H.P	Stage	NRV SIZE 65MM (2.5")	DISCHARGE IN LPM								PRICE
				575	550	520	490	420	300	240	180	PUMP SET
5RSMTM125-4	5.00	4		12	15	18	21	24	27	30	33	36740
5RSMTM125-5	6.00	5	TOTAL	15	20	23	25	30	34	37	40	40870
5RSMTM125-6	7.50	6	HEAD IN	20	24	27	30	36	42	45	48	47030
5RSMTM125-8	10.00	8	METERS	28	32	36	40	48	56	60	65	52975

NOTE: Above performance may varied on field conditions, bore well yield, bore well depth,
Cable selection & power fluctuations

